

AM
Your Ref : DOS/AJM/SM/EPA



Gladwins

Body Repair Centres

Derek Gladwin Ltd
Church Road, Warboys
Huntingdon. PE28 2RJ

Phone 01487 822427

Fax 01487 823142

email gladwinsbodyshop@aol.com

website www.gladwins.co.uk

Mr A Morley
Huntingdonshire District Council
Pathfinder House
St Marys St
Huntingdon
PE29 3TN

26th April 2002

Dear Mr Morley,

**Re: Environmental Protection Act-Part 1
Authorisation 24/93-Vehicle Respraying
Gladwins Ltd, Church Rd, Warboys**

Further to your letter of 11th April 2002.

I would like to confirm that all the paints used at our Warboys site, authorisation 24/93, are compliant coatings as required in Condition 10.

Please see attached specification sheet from our suppliers.

Yours sincerely

pp H.R. Death
Managing Director

Encs.



Company registered in
England no. 810899



R-M Phase 2 Compliant Product Portfolio 01-11-2000

This listing represents the R-M product portfolio commonly used to meet phase 2 V.O.C. maximums as detailed in the Secretary of State's Guidance Notes for the Respraying of Road Vehicles, PG 6/34. For further information please refer to Clause 32 of the PG 6/34 document. Appendix 2 of the process guidance notes contains a full list of materials commonly used in vehicle respraying, together with a detailed explanation of their respective functions and uses. All figures given are RFU values. Figures shown in brackets are maxima values from PG 6/34, Clause 32.

<u>Gunwash :-</u>	N/A	
<u>Precleaner :-</u>	PK 1000	VOC 195 g/ltr. (200 g/ltr.)
<u>Washprimer :-</u>	Eurofill	VOC 717 g/ltr. (780 g/ltr.)
<u>Precoat :-</u>	Hydroxyprimer	VOC 40 g/ltr. (250 g/ltr.)
<u>Primer Surfacer :-</u>	Excellfiller HD Hydrofiller	VOC 180 g/ltr. (250 g/ltr.) VOC 160 g/ltr. (250 g/ltr.)
<u>Wet on Wet Primer :-</u>	Express Sealer	VOC 495 g/ltr. (540 g/ltr.)
<u>Topcoat 1 Coat Conv. :-</u>	Uno HD 420	VOC <420 g/ltr. (420 g/ltr.)
<u>Topcoat 2 Coat C.O.B. :-</u>	Diamont 420 + Crystaltop HD 250	VOC <420 g/ltr. (420 g/ltr.)
	OR	
	Onyx HD (w/borne) + either Crystaltop HD 420 or Ultratop HD	VOC <420 g/ltr. (420 g/ltr.)
<u>Special Products :-</u>	Include Sealerplast 80, Special Mat 08, MT 849, R-M Flex, Uno Spot 80, BC 100, Antisilicone, Transparent Primer, SC 804.	



R-M Phase 2 Compliant Product Portfolio 01-11-2000

This listing represents the R-M product portfolio commonly used to meet phase 2 V.O.C. maximums as detailed in the Secretary of State's Guidance Notes for the Respraying of Road Vehicles, PG 6/34. For further information please refer to Clause 32 of the PG 6/34 document. Appendix 2 of the process guidance notes contains a full list of materials commonly used in vehicle respraying, together with a detailed explanation of their respective functions and uses. All figures given are RFU values. Figures shown in brackets are maxima values from PG 6/34, Clause 32.

<u>Gunwash :-</u>	N/A	
<u>Precleaner :-</u>	PK 1000	VOC 195 g/lt. (200 g/lt.)
<u>Washprimer :-</u>	Eurofill	VOC 717 g/lt. (780 g/lt.)
<u>Precoat :-</u>	Hydroxyprimer	VOC 40 g/lt. (250 g/lt.)
<u>Primer Surfacer :-</u>	Excellfiller HD Hydrofiller	VOC 180 g/lt. (250 g/lt.) VOC 160 g/lt. (250 g/lt.)
<u>Wet on Wet Primer :-</u>	Express Sealer	VOC 495 g/lt. (540 g/lt.)
<u>Topcoat 1 Coat Conv. :-</u>	Uno HD 420	VOC <420 g/lt. (420 g/lt.)
<u>Topcoat 2 Coat C.O.B. :-</u>	Diamont 420 + Crystaltop HD 250	VOC <420 g/lt. (420 g/lt.)
	OR	
	Onyx HD (w/borne) + either Crystaltop HD 420 or Ultratop HD	VOC <420 g/lt. (420 g/lt.)
<u>Special Products :-</u>	include Sealerplast 80, Special Mat 08, MT 849, R-M Flex, Uno Spot 80, BC 100, Antisilicone, Transparent Primer, SC 804.	