## **Decision Document**

Reference:	SR099689			
Applicant:	Encocam Ltd			
Address:	5 Stukeley Business Centre Blackstone Road Huntingdon			
		Cambridgeshire PE29 6EF		
_				
Installation	address:	5 Stukeley Busi	ness Centre Blackstone Road Huntingdon	
		Cambridgeshire PE29 6EF		
_		0		
Application	received:	14/03/2014		
Sufficient in		supplied: 20/0	03/2014	
Sufficient fe	ee: YES			
Commercia	l confident	iality request:	None made	
Commercial confider		iality decision:	N/A	
		-		
Application	consultati	on:		
Consultee:	Environn	nent Agency	Reason: Site previously had a COMAH	
status for ch	emicals.			
Consultation	n response	s:		
	Environment Agency Representation: Previous planning			
application				
Guidance N	otes: N	one for sector bu	t used PG3/06(04) Secretary of State's	
Guidance for	r Polishin	g or Etching Glas	s or Glass Products using Hydrofluoric Acid	
			cludes storage conditions for acids.	
		e permit available		
		e model/simple p		
		<b>*</b> *	- L	
Permit cond		tion: Reason		
	lition: R	eason		
1			micals are stored in adequate containers.	
	Т	o ensure that cher		
1		o ensure that cher o ensure any spill	micals are stored in adequate containers. ages are contained and can be cleaned up with on the environment.	
1	T T m	o ensure that cher o ensure any spill inimum impact o	ages are contained and can be cleaned up with	
1 2	T T m T	o ensure that cher o ensure any spill inimum impact o	ages are contained and can be cleaned up with on the environment.	
1 2	Tr Tr m Tr in	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation.	ages are contained and can be cleaned up with on the environment.	
1 2 3	T T m T in T	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the	
1 2 3	T T m T in T sy	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe ystem any spills a	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the	
1 2 3 4	T T m T in T sy T	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe ostem any spills a o ensure that arre	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified.	
1 2 3 4 5	T T m T in T sy T T	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe ystem any spills a o ensure that arre o ensure that HF	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly.	
1 2 3 4 5 6	Tr Tr In Tr In Tr Sy Tr Tr Tr	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe ystem any spills a o ensure that arre o ensure that HF	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets.	
1 2 3 4 5 6	Tr Tr In Tr Sy Tr Tr Tr Tr Tr Tr	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe o ensure that arre o ensure that arre o ensure that HF	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets.	
1   2   3   4   5   6   7	Tr Tr Tr Tr Tr Sy Tr Tr Tr Tr Tr Tr Tr Tr Tr	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe o ensure that arre o ensure that arre o ensure that HF	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets. emissions to atmosphere are clear from any	
1   2   3   4   5   6   7	Tr Tr In Tr In Tr Sy Tr Tr Tr Do Tr Do Tr Do	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe o ensure that whe o ensure that arre o ensure that HF o ensure that HF o ensure that the ollutants. o ensure that the o ensure that the o ensure that the o	ages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets. emissions to atmosphere are clear from any	
1     2     3     4     5     6     7     8	Trim Trim Trissy Tri Tri Tri Tri Do Tri bo	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe vstem any spills a o ensure that arre o ensure that arre o ensure that the ollutants. o ensure that the ollutants. o ensure that the o ensure that the o ensure that the o ensure that the	lages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets. emissions to atmosphere are clear from any operator can prove that inspections etc. have	
1     2     3     4     5     6     7     8	Tr Tr Tr Tr Tr Tr Sy Tr Tr Tr Dr Dr Si Tr Si	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe o ensure that whe o ensure that arre o ensure that arre o ensure that HF o ensure that the ollutants. o ensure that the o ensure that the	lages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets. emissions to atmosphere are clear from any operator can prove that inspections etc. have regulator knows what arrestment plant is on ctions will be taken in the event of any failure. problems are rectified quickly and efficiently	
1     2     3     4     5     6     7     8     9	Tr Tr Tr Tr Tr Tr Sy Tr Tr Tr Dr Dr Si Tr Si	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe o ensure that whe o ensure that arre o ensure that arre o ensure that HF o ensure that the ollutants. o ensure that the o ensure that the	lages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets. emissions to atmosphere are clear from any operator can prove that inspections etc. have regulator knows what arrestment plant is on ctions will be taken in the event of any failure.	
1     2     3     4     5     6     7     8     9	Trim Trim Trim Trissy Tri Tri Tri Do Tri Si Tri Si Tri Si	o ensure that cher o ensure any spill inimum impact o o ensure that no u stallation. o ensure that whe ystem any spills a o ensure that arre o ensure that arre o ensure that HF o ensure that the obliutants. o ensure that the cen undertaken. o ensure that the cen undertaken. o ensure that arre	lages are contained and can be cleaned up with on the environment. Inabated emissions are released from the en the IBC is being removed/plugged into the re notified and rectified. stment equipment is working correctly. isn't released in the droplets. emissions to atmosphere are clear from any operator can prove that inspections etc. have regulator knows what arrestment plant is on ctions will be taken in the event of any failure. problems are rectified quickly and efficiently	

12	To ensure that any abnormal emissions are rectified quickly to
	prevent unnecessary unabated emissions to atmosphere.
13	To ensure that the regulator can warn any local sensitive
10	receptors to take action, e.g. evacuate, if necessary.
14	To ensure that plant is not operated by untrained people.
	Untrained employees are more likely to have an accident that can
	result in unabated emissions to atmosphere.
15	To ensure that employees/managers/regulators know what
	training is required for new and current employees.
16	To ensure that relevant plant is working correctly.
17	To ensure that breakdowns are quickly rectified and reduces the
	potential for unabated emissions escaping to atmosphere.
18	Standard BAT Condition that is required to be placed on every
	environmental permit.
19	Standard BAT Condition that is required to be placed on every
	environmental permit.
Draft permit const	ultation
Date requested:	30/05/2014
Date responded:	09/06/2014
Response:	No issues with the draft permit.